

## **MS12: Quasi-brittle cracking in Concrete and Rock, including durability mechanics, coupled processes and hydraulic fracture**

**Gilles Pijaudier-Cabot<sup>1</sup>, Ignacio Carol<sup>2</sup>, Kaspar William<sup>3</sup>**

<sup>1</sup> Université de Pau et des Pays de l'Adour, Pau (FRANCE) (gilles.pijaudier-cabot@univ-pau.fr)

<sup>2</sup> Polytechnic University of Catalonia, Barcelona (SPAIN) (ignacio.carol@upc.edu)

<sup>3</sup> University of Houston, Houston (UNITED STATES) (kwillam@uh.edu)

Quasibrittle materials such as concrete or rock, when subject to mechanical action (either direct or indirectly induced by environmental effects), exhibit a transition from (visco) elastic response, to distributed micro-cracking, and coalescence to localized macro-cracking. In the approximately 3 decades since the term quasi-brittle was coined, a variety of models have been proposed. Models based on the continuum approach such as elasto-plasticity, continuum damage mechanics have been extensively developed. The process of localization into macro-cracks has been tackled either via “discrete cracking” (Fictitious crack model) or “smeared cracking” and associated regularization procedures with subsequent and size effect laws. A number of numerical techniques have emerged that try to reconcile all aspects of quasi-brittle material behavior, although no magic recipe seems to have been proposed as yet. Techniques such as zero-thickness interface elements or XFEM allow to integrate discrete cracks into background continuum meshes. Each one has its advantages and disadvantages, requiring in some cases, costly algorithms for re-meshing, crack tracking, etc.

Besides direct mechanical actions, cracking of concrete and geo-materials is often caused by environmental processes or flow/diffusion/transport-induced actions. All those problems have in common the need to solve coupled problems including mechanical and flow/diffusion/transport equations, although the degree of coupling may vary substantially from one case to another. This includes for instance (but not exclusively):

- (i) cracking of concrete-like materials due to differential volume changes due to durability-related phenomena such as drying shrinkage, sulfate attack, carbonation, alkali-silica-reaction, high temperatures.
- (ii) cracking (or opening of existing fractures) in rock masses due to fluid injections such as hydraulic fracture.

Quasi-brittle materials are heterogeneous in nature, and micro- or meso-mechanical models in which the heterogeneities are described explicitly are able to simplify considerably the constitutive description, and yet offer a much more powerful tool to represent the material behavior in simple and complex scenarios including not only complex mechanical scenarios but also combination of mechanical and diffusion-driven or coupled environmental actions.

This mini-symposium intends to gather contributions on all those and related topics, with a specific view to applications on concrete and rock.